

## **Fact Sheet – The myth of “clean coal”: why coal can only ever be dirty**

South Africa is the biggest coal producer in Africa. Over the past 10 years alone, we have produced an average of 254 million tons of coal per year. 70 million tons of the coal we produce is exported, and the rest is used locally.

Eskom burns about two-thirds of coal used in South Africa in its coal-fired power stations annually, while Sasol Synfuels uses about one-fifth. The rest is used in a variety of industries, including steel and cement manufacturing. The direct impacts of using coal on health, water, land, and the climate are devastating.

Proponents with vested interests in the survival of the coal industry are promoting the idea of “clean coal” technology as the lifeline that will allow governments to continue to depend on coal as an energy generation option, while supposedly limiting its risks and impacts.

There is no such thing as “clean coal”. An overview of the coal value chain (mining, production, supply, and disposal) proves that “clean coal” is **impossible**. There are no solutions to neutralise all - or even most - of the dire environmental, health, and climate change impacts caused by coal. This is especially so in the context of the significantly cleaner and cheaper alternative energy sources - such as wind and solar power - that are available in such abundance in our country.

### **What makes coal dirty?**

#### **Mining and processing of coal**

About 50% of the South Africa’s coal mines are opencast (at surface), while the rest are underground. The processes associated with either method of mining are inherently dirty with serious environmental and health implications. These include:

- loss of arable land;
- acid mine drainage, which pollutes surface and underground water;
- dust emissions, with dangerous particles inhaled by surrounding communities; and
- the production of 250 million tons per year of coal requires between 42.5 million m<sup>3</sup> (*enough to fill up 17 000 Olympic-sized swimming pools*) and 147 million m<sup>3</sup> (*enough to fill up to 58 800 Olympic-sized swimming pools*) of water.

**There are no methods that can avoid all or even most of the detrimental impacts of the mining and processing of coal, and no such methods will be available for the foreseeable future.**

#### **Combustion of coal**

**Water consumption:** In 2017, Eskom consumed approximately 307 million m<sup>3</sup> of water (*enough to fill 122 800 Olympic-sized swimming pools*) for power generation, amounting to 10 m<sup>3</sup> of water (*125 bathtubs*) per second (largely for cooling, and excluding the water used and polluted to produce or beneficiate the coal).

**Air pollution:** Also in 2017, Eskom’s coal-fired power stations also emitted the following types and quantities of atmospheric pollutants:

Pollutant	2016/17 emissions	Specific emissions (tons pollutant/GWh)
CO <sub>2</sub>	211.1 million tons	1051
SO <sub>2</sub>	1.766 million tons	8.79
NO <sub>x</sub>	0.885 million tons	4.26
PM <sub>10</sub>	65 130 tons	0.32
N <sub>2</sub> O	2782 tons	0.0138

Fine Particulate Matter (PM<sub>2.5</sub>) pollution from Eskom’s coal-fired power stations alone is responsible for the equivalent deaths of more than 2,200 South Africans every year, and causes thousands of cases of bronchitis and asthma in adults and children annually.

**If “clean coal” could be applied to the production of electricity using coal-fired power stations, it should mean the avoidance of all the impacts associated with the combustion of coal, or at least a very substantial reduction of the consumption of resources and impacts of the combustion process. This is not the case.**

The following three technologies (not all proven in SA) are generally relied on by “clean coal” proponents, but even combined, these will not provide the substantial reduction that is urgently needed. Instead, these technologies would generate harmful environmental impacts of their own.

### **1. Supercritical and ultra-supercritical (USC) boiler technology**

High Efficiency, Low Emissions (HELE) plants are put forward as the answer to greenhouse gas (GHG) emissions and pollution caused by coal-fired power plants. These are ultra-supercritical plants equipped with state-of-the-art pollution controls.<sup>[1]</sup>

**CO<sub>2</sub> emissions still remain high (at best reduced by about 20%); and pollutant (PM, SO<sub>2</sub>, and NO<sub>x</sub>) emissions also remain significant. HELE plants also require a significant increase in capital and operating costs, in a situation where coal power is already more expensive than available wind and solar power technologies.**

### **2. Circulating Fluidised Bed (CFB) combustion systems**

CFB systems can use lower-quality coal, including discard coal, using direct injection of lime into the furnace to control SO<sub>2</sub> emissions. Consequently, the amount of solid waste generated is significantly higher compared to pulverised fuel boilers (used by most of Eskom’s stations). For example, figures from the proposed Thabametsi Independent Power Producer (IPP) station show that for every 1000 tons of coal burnt, this CFB plant discharges 660 tons of ash and spent sorbent as waste. In addition, GHG emissions are significantly higher due to high Nitrous Oxide (N<sub>2</sub>O) emissions: 1.23 kg CO<sub>2</sub>eq per kWh.

**With 60 million tons accumulating every year, CFB technology cannot solve the discard coal problem. The use of discard coal in this way will also result in air pollution; the increase in the amount of water used to wash the discard coal; and an increase in the amount of ash and sorbent to be dumped because of the higher ash content. This coal ash contains toxic chemicals such as arsenic, lead, mercury, and chromium, which can cause, among other things, cancer, organ failure and brain damage.**

<sup>[1]</sup> ‘Supercritical’ and ‘ultrasupercritical’ plants operate at temperatures higher than the critical temperature (above this temperature, water turns to steam).

### **3. CO<sub>2</sub> disposal using Carbon Capture and Storage (CCS)**

CCS technology is considered to be a candidate to capture, inject, and permanently store CO<sub>2</sub> emissions (only) underground. There are several unresolved problems with CCS, including uncertainty around long-term leakage, its high capital costs, and the long lead-time - possibly decades - before the technology can be proven at the required scale.

**Although the South African Centre for Carbon Capture and Storage (SACCS) is attempting to demonstrate that CCS can actually be implemented using South African geology, it remains unproven. The bulk of Eskom's fleet of coal-fired power stations (12 of 15) are situated in the Mpumalanga Highveld, with two in Limpopo Province, and one in the Vaal Triangle, a far distance from the two identified possible storage sites to be tested.<sup>[2]</sup> This increase in transport costs would likely make large-scale CCS in South Africa unviable.**

**For further information** (also about emission control technologies, such as flue-gas desulphurisation) contact Annette Gibbs on 082 467 1295 – or CER Attorney, Tim Lloyd, at [tlloyd@cer.org.za](mailto:tlloyd@cer.org.za) or 083 275 2010 – at any time.

---

<sup>[2]</sup> The Zululand Basin in KwaZulu-Natal and the Algoa Basin in the Eastern Cape.